

LEITENBERGER
Mess- und Regeltechnik GmbH
Bahnhofstraße 32/33
D-72138 Kirchentellinsfurt
Fon: +49 (0)7121/908-0
Fax: +49 (0)7121/908-200
E-Mail: mrt-info@leitenberger.de

MB / MR
Pressure Gauge







Type	NG	A	C	D	F	G	H	K	SW
MB618....U MR638....U	63	28	6	68,3	13 - 10	1/4 SAE or 1/8 NPT	91	9	14
MB818....U MR838....U	80	29	6,3	86			105	9	14

High- and Low-Pressure Gauge pulsfree, dry,
with bottom connection, 2 scales for pressure bar + psi
4 coloured scales for refrigerants

Case:	Steel, PVC coated, blue/red
Window:	Plexiglass
Connection:	1/4 SAE or 1/8 NPT, bottom, Ms OT58
Elastic element:	C-Form, phosphor bronze
Movement:	Gearing, OT59 brass
Dial:	White
Pointer:	Black oxidized aluminiom
Range:	High pressue: -1/+38 bar / Low Pressure: -1/+18 bar
Accuracy:	Cl. 1,6
Ambient-T :	+15 / +65°C
Process fluid-T:	max. +65°C
Process pressure:	max. 75% of full scale value
Over pressure.:	25% of full scale value
Blow-out plug:	EPDM
Protection:	IP65 acc. to DIN EN 60529 / IEC29
Options on request:	- Scales for all marketable refrigerants - Glycerine filled - Other connectors

© 2014 / Leitenberger

ISO 9001:2008
Reg.no. 12 100 24343 TMS